

Содержание

Примеры конфигураций различных моделей коммутаторов для подключения IP-телефонов 2

WS-C6506-E 2

SNR-S2940-8G-v2 2

HPE V1910-48G 3

Примеры конфигураций различных моделей коммутаторов для подключения IP-телефонов

WS-C6506-E

```
switchport
switchport trunk encapsulation dot1q
switchport trunk native vlan 3
switchport trunk allowed vlan 3,2601
switchport mode trunk
switchport nonegotiate
switchport voice vlan 2601
load-interval 30
wrr-queue queue-limit 65 15 15
wrr-queue random-detect min-threshold 1 70 100 100 100 100 100 100 100
wrr-queue random-detect min-threshold 2 70 100 100 100 100 100 100 100
wrr-queue random-detect min-threshold 3 40 40 50 50 60 60 70 70
wrr-queue random-detect max-threshold 1 100 100 100 100 100 100 100 100
wrr-queue random-detect max-threshold 2 100 100 100 100 100 100 100 100
wrr-queue random-detect max-threshold 3 70 70 80 80 90 90 100 100
wrr-queue cos-map 2 1 1 2
wrr-queue cos-map 3 5 3 4
wrr-queue cos-map 3 7 6 7
no cdp enable
lldp enable
spanning-tree portfast edge trunk
```

SNR-S2940-8G-v2

```
lldp enable
Interface Ethernet1/7
description Yealink T31 (305)
lldp transmit med tlv capability
lldp transmit med tlv networkPolicy
network policy voice tag tagged vid 2601
spanning-tree portfast
switchport mode trunk
switchport trunk allowed vlan 3;2601
switchport trunk native vlan 3
```

HPE V1910-48G

```
undo voice vlan security enable
voice vlan track lldp
lldp enable

interface GigabitEthernet1/0/1
description Yealink-T31(1-306-01)
port link-type trunk
undo port trunk permit vlan 1
port trunk permit vlan 25 2601
port trunk pvid vlan 25
undo voice vlan mode auto
voice vlan 2601 enable
stp edged-port enable
```

From:

<https://kb.nstu.ru/> - База знаний НГТУ НЭТИ

Permanent link:

<https://kb.nstu.ru/it:voip:switches>

Last update: **2022/12/06 14:45**

